


# MUSTWALL 18B

## ACOUSTIC INSULATION FOR WALLS




HIGH PERFORMANCE AIRBORNE NOISE  
THERMAL ACOUSTIC INSULATION  
CONSISTING OF A COUPLED PANEL  
COMPOSED BY SBR RUBBER GRANULES AND  
A PLASTERBOARD LAYER



### ■ TECHNICAL SPECIFICATION

Pre-assembled 20 mm-thick acoustic insulation panels, made of a 7 mm-thick SBR (Stirene Butadiene Rubber) rubber granules layer, assembled with a 12.5 mm-thick plasterboard. The panels dimensions are 1.20 m width x 2.00 m length.



### ■ CERTIFIED ACOUSTIC IMPROVEMENT

CE product for acoustic insulation of existing walls and floors, Mustwall B reduces airborne noise between different apartments by improving acoustic comfort

### ■ FLEXIBILITY

Mustwall B can be applied to any wall or ceiling with acoustic and vibration-damping functions. High performances in little space

### ■ LAYING COSTS REDUCTION

Supplied already coupled to a plasterboard layer, Mustwall B ensures rapid and minimally invasive interventions in terms of dirt and dust production in environments

### ■ TO BE USED WITH

Wall solution for renovation and acoustic restoration of existing environments without any demolition work. Technical cavediums

### ■ TECHNICAL DATA

|                    |                        |
|--------------------|------------------------|
| Thickness          | 20 mm                  |
| Length             | 2,00 m                 |
| Width              | 1,20 m                 |
| Mass per unit area | 14,5 kg/m <sup>2</sup> |

|                      |                          |
|----------------------|--------------------------|
| Reaction to fire     | -                        |
| Thermal resistance R | 0,127 m <sup>2</sup> K/W |
| Transmission Loss Rw | 55 dB                    |

Wall composition - 250 mm thickness  
Coating side made with Mustwall 18B + 12.5 mm plasterboard  
on 200 mm clay block with 15 mm plaster on one side



# MUSTWALL 18B

## ACOUSTIC INSULATION FOR WALLS



### INSTALLATION INSTRUCTIONS FOR ACOUSTIC INSULATION FOR WALLS MUSTWALL 18B

**1** Lay the under wall stripe



**2** Lay points of a gypsum-based glue on the ground panel or use a low-expansion polyurethane glue



**3** Glue the panel to the wall pressing lightly



**4** Attach two safety plugs to the top of the panel



**5** Fix the second gypsum board with the glue and/or appropriate screws



**6** Apply the plastic mesh tape in the gypsum boards jointing lines. Grouting



**ACOUSTIC CERTIFICATES**  
Product acoustic certificates are available and allow to comply with the limits imposed by law



**INSTALLATION TEST**  
Acoustic performances of the intervention can be tested on site by a competent technician



**ACOUSTIC REPORT**  
Our technical staff is able to give you the proper support in all the project phases, supporting you in the identification of materials



**LAYING ASSISTANCE**  
Thanks to our extensive commercial technicians network, we are at your disposal for the coordination of the first laying phases on site

[SEE THE REFERENCES > VISIT THE WEBSITE](#)

[CONTACT THE TECHNICAL DEPARTMENT FOR MORE INFORMATION](#)



www.isolgomma.com  
PRG-MOD. 15 - REV. 5.0 01/07/21 EN

